


LUMINAIRE PHOTOMETRIC TEST REPORT


Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:

DATA OF LAMP		PHOTOMETRIC DATA Eff: 84.14 lm/W			
MODEL: HT-G75HBRRD8-918-XXL-ZZ1		Imax(cd)	541.3	S/MH(C0/180)	1.24
NOMINAL POWER(W)	18	LOR(%)	100.0	S/MH(C90/270)	1.24
RATED VOLTAGE(V)	120	TOTAL FLUX(lm)	1507.8	η UP,DN(C0-180)	0.0,49.6
NOMINAL FLUX(lm)	1507.8	CIE CLASS	DIRECT	η UP,DN(C180-360)	0.0,50.4
LAMPS INSIDE	1	η up(%)	0.0	CIBSE SHR NOM	1.25
TEST VOLTAGE(V)	120.0	η down(%)	100.0	CIBSE SHR MAX	1.35

LUMINOUS INTENSITY DISTRIBUTION DIAGRAM



C0 PLANE ISOLUX DIAGRAM (UNIT:lx)



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators:Nick
Test Date:14 September 2021

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance:1.906m [K=1.0000]
Remarks:

ZONAL FLUX DIAGRAM

ZONAL FLUX DIAGRAM:


γ	C0	C45	C90	C135	C180	C225	C270	C315	γ	Φ zone	Φ total	%lum, lamp
10	531.2	530.0	529.2	529.0	530.1	531.0	531.6	532.0	0- 10	51.15	51.15	3.39,3.39
20	500.1	498.4	496.5	496.1	498.3	499.9	501.4	501.8	10- 20	145.9	197.0	13.1,13.1
30	450.8	448.9	446.3	445.5	448.5	450.7	452.7	453.2	20- 30	219.4	416.5	27.6,27.6
40	386.6	384.5	381.7	380.6	384.2	386.6	389.0	389.5	30- 40	262.0	678.5	45,45
50	311.2	308.9	306.4	305.6	309.0	311.4	314.0	314.5	40- 50	269.0	947.5	62.8,62.8
60	227.9	226.1	224.1	223.1	226.5	228.8	231.1	231.3	50- 60	240.7	1188	78.8,78.8
70	141.6	140.5	139.5	138.6	141.3	143.3	145.3	145.3	60- 70	182.6	1371	90.9,90.9
80	60.73	60.50	60.48	59.60	61.23	62.61	64.13	63.73	70- 80	106.3	1477	98,98
90	2.399	2.540	2.287	2.475	1.106	1.337	1.198	0.6359	80- 90	30.61	1508	100,100
100	0.0039	0	0	0.0016	0.0042	0.0040	0.0019	0.0007	90-100	0.1010	1508	100,100
110	0.0040	0	0	0.0023	0.0014	0.0011	0.0028	0.0026	100-110	0.0019	1508	100,100
120	0.0065	0.0005	0	0.0035	0.0012	0	0.0033	0.0030	110-120	0.0018	1508	100,100
130	0.0077	0.0053	0	0.0025	0	0	0.0011	0.0026	120-130	0.0019	1508	100,100
140	0.0033	0.0065	0	0.0012	0.0021	0	0	0.0026	130-140	0.0020	1508	100,100
150	0.0097	0.0014	0.0033	0.0012	0.0022	0.0011	0.0014	0.0021	140-150	0.0019	1508	100,100
160	0.0028	0	0.0002	0.0018	0	0.0017	0.0028	0.0003	150-160	0.0010	1508	100,100
170	0	0	0.0033	0.0030	0.0007	0	0	0.0039	160-170	0.0003	1508	100,100
180	0	0	0	0	0	0	0	0	170-180	0.0001	1508	100,100
DEG	LUMINOUS INTENSITY:cd									UNIT:lm		

C Range: 0 - 360DEG
 C Interval: 22.5DEG
 Test Speed: HIGH
 Temperature: 25.1DEG
 Operators:Nick
 Test Date:14 September 2021

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
 Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.353
 Humidity: 56.8%
 Test Distance:1.906m [K=1.0000]
 Remarks:

LUMINANCE LIMITATION CURVES

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

CU AND LUMINAIRE BUDGETARY ESTIMATE DIAGRAM

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0
p _w	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
p _{fc}	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Coefficients of Utilization(CU)									
0.0	1.19	1.19	1.19	1.16	1.16	1.16	1.11	1.11	1.11	1.06	1.06	1.06	1.02	1.02	1.02	.00
1.0	1.04	.00	.96	1.02	.98	.94	.97	.94	.91	.93	.91	.88	.90	.88	.86	.84
2.0	.90	.84	.78	.89	.82	.77	.85	.80	.75	.82	.77	.73	.79	.75	.72	.70
3.0	.79	.71	.65	.78	.70	.64	.75	.68	.63	.72	.66	.62	.69	.65	.61	.59
4.0	.70	.62	.55	.69	.61	.54	.67	.59	.54	.64	.58	.53	.62	.57	.52	.50
5.0	.63	.54	.47	.62	.53	.47	.60	.52	.46	.58	.51	.46	.56	.50	.45	.43
6.0	.57	.48	.41	.56	.47	.41	.54	.46	.41	.52	.45	.40	.51	.45	.40	.38
7.0	.51	.43	.36	.51	.42	.36	.49	.41	.36	.48	.41	.36	.46	.40	.35	.33
8.0	.47	.38	.32	.46	.38	.32	.45	.37	.32	.44	.37	.32	.42	.36	.32	.30
9.0	.43	.35	.29	.42	.35	.29	.41	.34	.29	.40	.34	.29	.39	.33	.29	.27
10.0	.40	.32	.26	.39	.32	.26	.38	.31	.26	.37	.31	.26	.36	.30	.26	.24



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

WEC AND CCEC

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:

pcc	80%			70%			50%			30%			10%			0	
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0	
pfc	20%			20%			20%			20%			20%			0	
RCR	RCR:Room Cavity Ratio						Wall Exitance Coefficients (WEC)										
0.0																	
1.0	.310	.177	.056	.303	.173	.055	.290	.166	.053	.278	.160	.051	.267	.155	.050		
2.0	.292	.160	.049	.285	.157	.048	.274	.152	.047	.263	.147	.046	.253	.143	.045		
3.0	.270	.143	.043	.264	.141	.043	.254	.138	.042	.244	.134	.041	.235	.130	.040		
4.0	.249	.129	.038	.244	.128	.038	.235	.124	.037	.226	.121	.037	.218	.119	.036		
5.0	.230	.117	.034	.226	.116	.034	.217	.113	.033	.210	.111	.033	.203	.108	.033		
6.0	.213	.107	.031	.209	.106	.030	.202	.104	.030	.195	.101	.030	.189	.099	.030		
7.0	.198	.098	.028	.195	.097	.028	.189	.095	.027	.182	.094	.027	.177	.092	.027		
8.0	.185	.091	.025	.182	.090	.025	.176	.088	.025	.171	.087	.025	.166	.085	.025		
9.0	.174	.084	.023	.171	.083	.023	.166	.082	.023	.161	.081	.023	.156	.079	.023		
10.0	.163	.078	.022	.161	.078	.022	.156	.076	.022	.152	.075	.021	.148	.074	.021		

pcc	80%			70%			50%			30%			10%			0
pw	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	50%	30%	10%	0
pfc	20%			20%			20%			20%			20%			0
RCR	RCR:Room Cavity Ratio						Ceiling Cavity Exitance Coefficients (CCEC)									
0.0	.191	.191	.191	.163	.163	.163	.111	.111	.111	.064	.064	.064	.020	.020	.020	
1.0	.180	.156	.134	.154	.134	.116	.106	.092	.080	.061	.053	.047	.019	.017	.015	
2.0	.172	.132	.098	.148	.114	.085	.101	.079	.059	.058	.046	.035	.019	.015	.011	
3.0	.164	.114	.074	.141	.099	.065	.097	.069	.045	.056	.040	.027	.018	.013	.009	
4.0	.157	.101	.058	.135	.087	.051	.093	.061	.036	.054	.036	.021	.017	.012	.007	
5.0	.149	.091	.047	.128	.078	.041	.088	.055	.029	.051	.032	.017	.016	.010	.006	
6.0	.142	.082	.039	.122	.071	.034	.084	.050	.024	.049	.029	.014	.016	.010	.005	
7.0	.135	.075	.033	.116	.065	.029	.080	.046	.021	.047	.027	.012	.015	.009	.004	
8.0	.129	.070	.029	.111	.060	.025	.077	.042	.018	.045	.025	.011	.014	.008	.004	
9.0	.123	.065	.025	.106	.056	.022	.073	.039	.016	.043	.023	.009	.014	.008	.003	
10.0	.117	.060	.023	.101	.052	.020	.070	.037	.014	.041	.022	.008	.013	.007	.003	

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

UGR(Unified Glare Rating) Table

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm											
NAME: HT-G75HBRRD8-918-XXL-ZZ1					TYPE:			WEIGHT:			
SPEC.:					DIM.:			SERIAL No.:			
MFR.: hengte					SUR.:			Shielding Angle:			
ceiling/cavity	0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3	
walls	0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3	
working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	
Room dimensions		Viewed crosswise					Viewed endwise				
x = 2H y = 2H		18.2	19.7	18.5	19.9	20.1	18.1	19.7	18.4	19.9	20.1
	3H	19.7	21.1	20.0	21.3	21.6	19.6	21.0	19.9	21.3	21.5
	4H	20.3	21.6	20.6	21.9	22.1	20.2	21.6	20.5	21.8	22.1
	6H	20.7	22.0	21.1	22.3	22.6	20.7	21.9	21.0	22.2	22.5
	8H	20.9	22.1	21.2	22.4	22.7	20.8	22.0	21.2	22.3	22.6
	12H	21.0	22.1	21.3	22.4	22.7	20.9	22.1	21.3	22.4	22.7
4H	2H	18.8	20.1	19.1	20.4	20.6	18.7	20.1	19.1	20.3	20.6
	3H	20.5	21.7	20.8	21.9	22.3	20.4	21.6	20.8	21.9	22.2
	4H	21.2	22.3	21.6	22.6	22.9	21.2	22.2	21.5	22.5	22.9
	6H	21.8	22.7	22.2	23.1	23.4	21.7	22.7	22.1	23.0	23.4
	8H	22.0	22.9	22.4	23.2	23.6	21.9	22.8	22.3	23.2	23.6
	12H	22.1	22.9	22.5	23.3	23.7	22.1	22.9	22.5	23.3	23.7
8H	4H	21.5	22.4	21.9	22.7	23.1	21.4	22.3	21.8	22.7	23.1
	6H	22.2	22.9	22.6	23.3	23.8	22.2	22.9	22.6	23.3	23.7
	8H	22.5	23.1	22.9	23.6	24.0	22.4	23.1	22.9	23.5	24.0
	12H	22.7	23.3	23.2	23.7	24.2	22.7	23.2	23.1	23.7	24.1
12H	4H	21.5	22.3	21.9	22.7	23.1	21.4	22.3	21.9	22.6	23.0
	6H	22.3	22.9	22.7	23.3	23.8	22.2	22.9	22.7	23.3	23.7
	8H	22.6	23.1	23.1	23.6	24.1	22.5	23.1	23.0	23.6	24.0
Variations with the observer position at spacings:											
S = 1.0H	+ 0.2 / - 0.2					+ 0.2 / - 0.2					
1.5H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					
2.0H	+ 0.2 / - 0.3					+ 0.2 / - 0.3					

CIE Pub.117 Corrected 1508 lm Total Lamp Luminous Flux. (8log(F/F0) = 1.4)

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

UTILIZATION FACTORS TABLE

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:


REFLECTANCE										
Ceiling	0.8	0.8	0.8	0.7	0.7	0.7	0.5	0.5	0.5	0
Walls	0.7	0.5	0.3	0.7	0.5	0.3	0.7	0.5	0.3	0
Working plane	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0
ROOM INDEX	UTILIZATION FACTORS (PERCENT) $k(RI) \times RCR = 5$									
$k = 0.60$	58	46	39	57	46	39	56	45	39	33
0.80	68	56	49	67	56	49	65	55	48	41
1.00	76	65	58	75	64	57	73	66	57	50
1.25	83	73	66	82	72	65	79	71	64	57
1.50	88	78	71	87	77	71	83	76	70	62
2.00	95	86	80	93	85	79	90	83	78	70
2.50	99	91	85	97	90	84	93	87	82	74
3.00	102	95	90	100	94	89	96	91	87	78
4.00	106	101	96	104	99	94	100	95	92	83
5.00	109	104	100	106	102	98	102	98	95	86
ROOM INDEX	UF (total)									Direct
According to DIN EN 13032-2 2004			Suspended					SHRNOM = 1.25		

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

ISOCANDELA DIAGRAM

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:




C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators:Nick
Test Date:14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance:1.906m [K=1.0000]
Remarks:

AAI CURVES

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:




Note: The Curves indicate the illuminated area and the average illumination when the luminaire is at different distance.

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

ISOLUX DIAGRAM

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

LED Avg.L Report

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:


AvgL	cd/m2
L_0~180 (65) av	4359
L_0~180 (75) av	3848
L_0~180 (85) av	3030
L_90~270 (65) av	4375
L_90~270 (75) av	3895
L_90~270 (85) av	3111
L_45 (65) av	4366
L_45 (75) av	3872
L_45 (85) av	3079

Standard: GB/T 29293-2012

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

Planar Illuminance Curve



C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators: Nick
Test Date: 14 September 2021

γ Range: 0 - 180DEG
 γ Interval: 1.0DEG
Test System: EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance: 1.906m [K=1.0000]
Remarks:

LUMINOUS DISTRIBUTION INTENSITY DATA

Test:U:120.0V I:0.1503A P:17.92W PF:0.9931 Freq:60.01Hz Lamp Flux:1507.8x1 lm		
NAME: HT-G75HBRRD8-918-XXL-ZZ1	TYPE:	WEIGHT:
SPEC.:	DIM.:	SERIAL No.:
MFR.: hengte	SUR.:	Shielding Angle:

Table--1

UNIT: cd

C (DEG) γ (DEG)	0	22.5	45	67.5	90	112.5	135	157.5	180	202.5	225	247.5	270	292.5	315	337.5			
0	541	541	541	541	541	541	541	541	541	541	541	541	541	541	541	541			
5	539	539	538	538	538	538	538	538	538	538	539	539	539	539	539	539			
10	531	530	530	530	529	529	529	529	530	530	531	531	532	532	532	532			
15	518	517	517	516	515	515	515	515	517	517	518	519	519	519	519	519			
20	500	499	498	497	497	497	496	496	498	499	500	501	501	501	502	501			
25	478	477	476	474	473	473	473	473	475	476	477	478	479	479	480	479			
30	451	450	449	447	446	446	445	446	448	449	451	452	453	453	453	453			
35	420	419	418	417	416	415	415	415	418	419	420	421	422	423	423	423			
40	387	385	384	383	382	381	381	381	384	385	387	388	389	389	389	389			
45	350	349	348	346	345	344	344	345	348	349	350	351	353	353	353	353			
50	311	310	309	307	306	306	306	306	309	310	311	313	314	314	314	314			
55	270	269	268	267	266	265	265	265	268	269	271	272	273	273	274	273			
60	228	227	226	225	224	223	223	223	226	227	229	230	231	231	231	231			
65	185	184	183	182	182	181	181	181	184	185	186	187	188	188	188	188			
70	142	141	141	140	139	139	139	138	141	142	143	144	145	145	145	145			
75	99.6	99.2	99.1	98.8	98.6	98.0	97.5	97.3	99.6	100	101	102	103	103	103	102			
80	60.7	60.4	60.5	60.5	60.5	59.9	59.6	59.2	61.2	61.8	62.6	63.4	64.1	64.0	63.7	63.1			
85	25.8	25.7	25.8	25.8	25.7	25.6	25.3	25.1	27.0	27.4	27.9	28.3	28.5	28.4	28.3	28.0			
90	2.40	2.53	2.54	2.40	2.29	2.33	2.47	2.51	1.11	1.16	1.34	1.39	1.20	0.87	0.64	0.63			
95	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
100	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
105	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
110	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
115	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
120	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01			
125	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01			
130	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01			
135	0.01	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01			
140	0.00	0.01	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.01			
145	0.01	0.01	0.01	0.00	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
150	0.01	0.01	0.00	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
155	0.01	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
160	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
165	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
170	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
175	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			
180	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00			

C Range: 0 - 360DEG
C Interval: 22.5DEG
Test Speed: HIGH
Temperature: 25.1DEG
Operators:Nick
Test Date:14 September 2021

γ Range: 0 - 180DEG
γ Interval: 1.0DEG
Test System:EVERFINE GO-R5000_V2 SYSTEM V2.0.353
Humidity: 56.8%
Test Distance:1.906m [K=1.0000]
Remarks: